

Roller Rail Plus for shaftless decoiling

Produktvorteile auf einem Blick:

- ✓ shaftless decoiling
- ✓ Accommodates many drum sizes
- ✓ Stepless adjustment of drum width
- ✓ Quick assembly and disassembly
- ✓ Tool-free operation
- ✓ Low weight
- ✓ Space-saving transport
- ✓ Robust construction



For more
product info



The Roller Rail Plus features a lightweight and robust aluminium base frame with ball-bearing rollers, a front run-up surface, three locking positions for different drum sizes and a roller locking function. It enables optimal, shaftless decoiling of cable drums through fast, safe and tool-free operation.

The compact design, low weight and synthetic handles on the sides make it easy to transport. The fastening holes allow the roller rail to be either permanently fixed with screws or temporarily fastened to soft ground with ground nails. The optionally available connection set supports the stability and positioning of the roller rail during the decoiling process even without fixing to the ground. Anti-slip coverings also ensure optimum grip on smooth floor surfaces. When the cable drums are placed in the roller rail, the transverse grooves on the inclined surface ensure a firm grip. The rollers run on dust- and dirt-protected ball bearings and can be adjusted to three different locking positions without tools. The high side edge ensures safe drum guidance. The drum width is also infinitely adjustable. The roller lock function can be unlocked while standing and thus enables easy removal of the cable drum.

Two pieces are required for correct use.





Roller Rail Plus for shaftless decoiling

Roller Rail Plus



Roller Rail Plus


Aluminium roller rail for shaftless decoiling of drums. Tool-free displacement of the reel in 3 locking positions. Stepless adjustment of the drum width. Simple roller locking function for drum removal.

2 pieces are needed for the application.

Dimension (LxWxH) 1000x138x134 mm

Drum-Ø	Ultimate load/Pair	Weight	Art. No.
Ø 450-1600 mm	1000 kg	7,4 kg	107030

Connection-Set Roller Rail Plus



Connection-Set Roller Rail Plus

Aluminium connection tube with two clamping pieces for tool free and steplessly adjustment of the drum width. For additional stability and reliable positioning.

Dimension (LxWxH) 1190x50x96 mm

Connection tube Ø	Metal thickness	Weight	Art. No.
Ø 27 mm	4 mm	2,8 kg	107031